



Declaration of Performance

1. *Unique identification of product type:*

**Ketley Quarry Tile
Group HD, Category II, 215x102.5x18mm Clay Masonry Units**

2. *Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):*

KPT

3. *Intended use or uses of the construction product in accordance with the applicable harmonised technical specification as foreseen by the manufacturer:*

Clay Quarry tiles for internal and external uses for rigid forms of construction

4. *Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):*

Ketley Brick Company Ltd, Dreadnought Works, Pensnett, Brierley Hill, West Midlands. DY5 4TH

5. *System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*

System 4

6. *Declared performance:*

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerances	Meets Requirements For extruded tiles Group A1b	BS EN 14411:2012
Water Absorption	≤3.0%	BS EN 14411:2012
Frost Resistance	Complies after 100 cycles	BS EN 14411:2012
Breaking Strength	≥1100 N	BS EN 14411:2012
Slip/Skid resistance (Pendulum)	Rz Value 20+µm PTV Value 36+ (Low Slip Potential)	BS 7976-2:2002
Stain Resistance	Minimum Class 3	BS EN 14411:2012
Deep Abrasion Resistance(Unglazed)	≤275mm³	BS EN 14411:2012
Slip Resistance (Wet Barefoot Ramp)	Category C	DIN 51097:1992
Slip Resistance (Shod Ramp)	R11	DIN 51130:2010

7. *The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 6.*

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer:

Name: *Alex Patrick-Smith*

Signed:

Date: 09.05.2016