

Ketley Patterned Staffordshire Clay Pavers

Specification Sheet



Performance Standard: BS EN 1344:2002

Ketley Staffordshire Pavers are produced at our works located in the heart of the Black Country. They have been made from our own Etruria Marl since Victorian times. Their unrivalled physical properties include their strength, durability and permanence of colour.

Work Size mm	Pattern	Pack Weight	No per pallet	Units/m ² Rigid with 10mm joint	Units/m ² Flexible butt jointed (3mm joint)
220x105x50	Diam cheq/ 2 Panel/ 8 panel/star	1300kg	500	38	42
200x100x50	Diam cheq/ 2 Panel/ 8 panel/star	1150kg	500	43	48
220x105x65	Diam cheq/ 2 Panel/ 8 panel/star	1360kg	400	38	42
200x100x65	Diam cheq/ 2 Panel/ 8 panel/star	1200kg	400	43	48

Colour	Staffordshire Blue, Staffordshire Brown Brindle, Staffordshire Red
Raw Material	Etruria Marl Clay
Manufacture	Extruded, Wirecut and fired above 1130°C
Bulk Density	2,300kg/m ³
Texture	Patterned
Size, Tolerance	BS EN 1344: 2002
Size Range	R1
Mean Transverse Breaking Load	T4
Unpolished Slip/Skid Resistance	U3
Abrasion Resistance	A3
Freeze/Thaw Resistance	FP100

Ketley Brick Company Ltd
Dreadnought Works, Pensnett, Brierley Hill, West Midlands, DY5 4TH, UK
Tel: 01384 78361 Fax: 01384 74553 Email: info@ketley-brick.co.uk Web: www.ketley-brick.co.uk
Ketley Brick Company Ltd. is a company registered in England and Wales with Reg number 699040.